SAFETY DATASHEET

1. Identification of the substance/preparation and of the company/undertaking

Date issued	25/09-2012
Product name	Active Rust Primer 662 SG (Enviro-coat 2000)
Use of the substance/preparation	Waterborne, naturally drying, rust converting acrylic primer, rust-preventing primer.
Importer	
Company name	Nortrade AS
Postal address	PO box 181
Postcode	4662
Place name	Kristiansand
Country	NORWAY
Tel	+4738023079

E-mail enviro-coat@nortrade.no
Prepared by Hydro Production Partner AS (Norsk Hydro ASA), Roar Eriksen

Emergency telephone tel:+47 38 02 30 79

2. Composition/information on ingredients

CAS no.	EC no.	Component name	Contents	Labelling/classification
112-34-5	203-961-6	2-(2-Butoxyethoxy)ethanol	1- 2.5 %	Xi; R36
		A preparation of aqueous solution of acrylic copolymers.	0- 1 %	Xi; R36/38
Column head	dings	inventory of Existing Comme as specified in the substance	ercial Chemical Substan e list (substances that a ssible). Contents given i	or Elincs number) = European ces; Ingredient name = Name re not included in the substance n; %, %wt/wt, %vol/wt, %vol/vol,
HH/HF/HE		T+ = Very toxic, T = Toxic, C Explosive, O = Oxidizing, F+ Environmental hazard		
Component of	comments	See section 16 for the full te	xt of the R Phrases decl	ared above.

3. Hazards identification

4	Fire	aid	measure	26

Inhalation	If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.
Skin contact	In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.
Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.
Ingestion	Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately.

5. Fire-fighting measures

Suitable extinguishing media	In case of fire, use water spray (fog), foam, dry chemical, or CO2.
Fire and explosion hazards	No specific hazard.
Personal protection equipment	Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

6. Accidental release measures		
Personal precautions	Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment (Section 8). Follow all fire fighting procedures (Section 5).	
Environmental precautions	Minimize contact of spilled material with soils to prevent runoff to surface waterways. See Section 13 for Waste Disposal Information.	
Methods for cleaning	If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) scoop up material and place in a sealed, liquid-proof container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.	

7. Handling and stora	ge
Handling	Keep to the general safety and health regulations and to good housekeeping standards. Always keep the product in containers made of the same material as the supply container. See Section 8 for personal protection.
Storage	Observe label precautions. Store in a cool (5 - 45°C) dry, well ventilated place away from sources of heat, ignition and direct sunlight.

8. Exposure controls/personal protection

Exposure controls

Occupational exposure controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are proximal to the work-station location.
Respiratory protection	A respirator is not needed under normal and intended conditions of product use.
Hand protection	Use latex gloves. Penetration time is not tested for this material, change gloves often. The penetration time might vary with exposure time, the type of work and the thickness of the glove material. Change gloves frequently.
Eye protection	Safety glasses.
Skin protection (other than of the hands)	Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable suits).
Other Information	Wash hands after handling compounds and before eating, smoking, using lavatory, and at the end of day. All personal protective equipment shall be CE-marked.

9. Physical and chemical properties

Physical state	Liquid.
Odour	Mild
Colour	Beige.
Solubility description	Soluble in water.
Specific gravity	Value: 1.05-1.10 g/cm ³ Comments: (20 °C)
Boiling point	Value: 100 °C
pH (as supplied)	Value: 2-4
Flash point	Comments: N.A.
Explosion limit	Comments: N.A.
Spontaneous combustability	Comments: N.A.
Vapour pressure	Comments: Weighted average: 0.04 kPa (0.3 mm Hg) (at 20°C)
Viscosity	Value: 400-474 cP Comments: at 20 °C

10. Stability and reactivity

Materials to avoid	Slightly reactive to reactive with oxidizing agents.
Hazardous decomposition products	Not known

Stability The product is stable.

11. Toxicological information

Components' toxicological data

Component	2-(2-Butoxyethoxy)ethanol
LD50 oral	Value: > 2000 mg/kg Test animal species: Rat
LD50 dermal	Value: > 2000 mg/kg

Component Aqueous solution of acrylic copolymer

LD50 oral Value: > 5000 mg/kg
Test animal species: Rat

Other information regarding health hazards

Inhalation At normal use or storage there is no evaporation from the product.

Skin contact May cause slight irritation.

Eye contact May cause temporary eye irritation.

Ingestion May cause some irritation to mouth, throat and stomach.

12. Ecological information

Components' toxicological data

Component	2-(2-Butoxyethoxy)ethanol
Acute aquatic, fish	Value: 1805 mg/l Test method: Not known Species: Not known Duration: 48 hours
Acute aquatic, Daphnia	Value: 3200 mg/l Test method: Not known Species: Not known Duration: 24 hours
Component	Aqueous solution of acrylic copolymer
Acute aquatic, fish	Value: 72 mg/l Test method: Not known Species: Not known Duration: 96 hours
Acute aquatic, Daphnia	Value: > 100 mg/l Test method: Not known Species: Not known Duration: 48 hours

Other ecological information

Persistence and degradability	The degradability of the product has not been stated. 2-(2-Butoxyethoxy)ethanol: This product is readily biodegradable.
Bioaccumulative potential	The product is not expected to bioaccumulate.
Environmental details, conclusion	The product is not known to represent any danger for the environment.

Primary irritant effect

- on the skin:	No irritant effect.
- on the eye:	No irritant effect.
- sensitization:	No sensitizing effects known.
Additional toxicological infomation	The product is not subject to classification according to the calculation method of the General EU Classification Gudidelines for Preparations as issued in the latest version. When used and handled according to specifications, the product does not have any harmful effects to our experience.

13. Disposal considerations

Product classified as hazardous waste	No,
Packaging classified as hazardous waste	No,
Specify the appropriate methods of disposal	The generation of waste should be avoided or minimised wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

14. Transport information

Other applicable information. Not classified as dangerous goods.

15 .	R	eau	atory	∕ inf	forma	tion
			at O I			

Composition on the label	2-(2-Butoxyethoxy)ethanol: 1 - 2.5 %
Other annotations	This product is not classified according to the EU regulations.
References (laws/regulations)	Norsk Stoffliste 2005 (The Norwegian Pollution Control Authority, The Norwegian Labour Inspection Authority, The Directorate for Civil Protection and Emergency Planning). Administrative normer for forurensning i arbeidsatmosfære (The Norwegian Labour Inspection Authority, best. nr. 361), ADR, RID, IMDG, IATA, Micromedex Tomes CPS System. Forskrift om utarbeidelse, distribusjon m.v. av helse-, miljø og sikkerhetsdatablad. Forskrift om farlig avfall med vedlegg (2003). Forskrift om klassifisering, merking m.v. av farlige kjemikalier (2005). Arbeidstilsynets brosjyre om løsemidler (The Norwegian I abour Inspection Authority).

4.0	6 4				4 .
16.	Ot	ner	ınt	orma	tion

List of relevant R-phrases (in section 2)	R36 Irritating to eyes. R36/38 Irritating to eyes and skin.
Further information	EU limit for this product (Cat A/i): 140 g/l VOC (2010) This product contains: 20 g/l VOC Norway: YL-group: 00 Denmark: VOC coding: 00-1
Supplier's notes	The safety data sheet has been approved in accordance with the regulations in force. Hydro Production Partner is not responsible for any errors or deficiencies in the information received from the manufacturer/ supplier. The manufacturer/ supplier mentioned in section 1 is legally responsible for the contents of the safety data sheet.